

## FLON®

### Broadcast Cables LC

-90°C / +200°C

Standart Analog Video Kablosu - 75 Ohm Koaks.

Standard Analog Video Cable - 75 Ohm Coax.

- 1- İletken: Solid (mono) bakır tel.
- 2- İzolasyon: FEP izolasyon.
- 3- Örgü: Çıplak bakır örgü %97 kapama.
- 4- Kılıf: Siyah FEP kılıf.

- 1- Conductor: Solid bare copper wire.
- 2- Insulation: FEP insulation.
- 3- Braid: Bare copper braid %97 coverage.
- 4- Sheath: Black FEP jacket.

#### Ambalaj

- Kargal, plastik makara, tahta makara veya YAPIBOX koli tipi fiçilerde.

#### Packing

- Rolls, spools, drums or YAPIBOX.

#### Uygulama Alanları

- Görüntü kablosudur.

#### Applications

- Broadcasting cable.

#### Karakteristik Özellikleri

- Plenum tip.

#### Characteristics

- Plenum type.

#### Elektriksel

- Çalışma Gerilimi: 300 V.

#### Electrical

- Working voltage : 300 V.



C

ÜRÜN KODU PRODUCT CODE	Nominal kesit alanı Nominal cross-section core Ø AWG	Nominal damar çapı Nominal core OD mm	Nominal kablo çapı Nominal outer diameter mm	Maks. sin. zayıflaması Max. atten dB/100m	Nominal empedans Nom imp. (Ohm)	Nominal kapasitans Nom capacitance pF/m	Nom. sinyal zayıflaması Nom attenuation	
							MHz	dB/100 mt
188241	1 x AWG23	3.35	4.83	2.20	75.0	64	1	1,60
FEP * FEP				6.0		25,0	10	3,30
Jacket				8.5		25,0	50	7,50
High and low temperature				10.7		23,6	100	10,80
				15.4		21,5	200	17,10
				19.8		20,1	400	27,60
				29.0		18,0	700	38,00
				32.80		17,3	900	45,30
							1.000	48,50